

## INDOOR - BATHROOM (VENTILATING MOISTURE CONTROL BATHROOM CEILING MOUNTED DUCT)

Model Name		FPRSQ20APV1	
Power Supply		V/Ph/Hz	220-240V/1Phase/50Hz
Cooling Capacity		Kw	1.95
Standard Mode	Power Consumption (With Water Drain Pump)	W	54
	Air Flow Rate (Hi/Lo)	m3/min	7-Mar
	Sound Level (Hi/Lo)	dB(A)	43/26
Dry Mode	Power Consumption (With Water Drain Pump)	W	85
	Air Flow Rate (Hi/Lo)	m3/min	7
	Sound Level (Hi/Lo)	dB(A)	43
Fan Only Mode	Power Consumption (With Water Drain Pump)	W	35
	Air Flow Rate (Hi/Lo)	m3/min	07/03
	Sound Level (Hi/Lo)	dB(A)	45/28
Ventilation Mode	Air Flow Rate (Hi/Lo)	m3/min	5/2.1
	Sound Level (Hi/Lo)	dB(A)	40/24
Dimension	Unit Dimention (HxWxD)	mm	230 x 555 x 540
	Panel Dimension (HxWxD)	mm	60 x 625 x 640
	Discharge Dimension (HxWxD)	mm	320 x 60
Unit Weight (Body/Panel)		kg	22/2.5
Sound Level (Hi/Med/Low)		dB(A)	42/25
Piping Connections	Liquid Pipe/Gas Pipe	mm	φ6.4/φ12.7
	High and Low Pressure Pipe	mm	φ9.5
	Condensate Drain Pipe	mm	PVC26(0.Dφ26/I.D.φ20)
Decorative Panel		BYEBP20W1E	
Wired Remote Controller		BRC62A612	