

INDOOR - LONG DUCT (MEDIUM STATIC CEILING MOUNTED DUCT)

Model Name		FPSQ50CV1	FPSQ63CV1	FPSQ80CV1	FPSQ100CV1	FPSQ125CV1	FPSQ140CV1
Power Supply	V/Ph/Hz	220-240V/1Phase/50Hz					
Cooling Capacity	Kw	5.6	7.1	9	11.2	14	16
Power Consumption	W	118	151	194	228	274	325
Power Consumption	With Water Drain Pump						
Air Flow Rate (Hi/Med//Lo)	m ³ /min	17.6/14.9/12.3		23.8/19.6/15.5	28.0/23.1/18.2	33.0/27.8/22.5/	39.0/32.2/25.4
Sound Level (Hi/Med/Lo)	dB(A)	35/32/29		37/34/31	40/37/34	42/39/36	
ESP (Hi/Lo)	mm	80/50		100/50		80/50	
Unit Dimension (HxWxD)	mm	250 x 1000 x 700		250 x 1400 x 700			
Discharge Dimension (HxW)	mm	200 x 962		200 x 1362			
Unit Weight	kg	32		40	42		
Piping Connections	Liquid Pipe/Gas Pipe	φ6.4/φ12.7		φ9.5/φ15.9			
	Condensate Drain Pipe	PVC32(0.D.φ26/I.D.φ20)					
Wired Remote Controller		BRC1E632					